

DATA SHEET
TUBE PE SH

1. PRODUCT PROPERTIES ¹

Parameter	Value	Deviation	Unit	Methodology
Thickness	≤ 35 > 35	2σ ± 8% 2σ ± 5%	μ	PN-ISO 4593
Width	<800 800-1500 >1500	± 10 ± 15 ± 20	mm	PN-ISO 4592
Gusset	Suited towards customer's needs			
Density	932	± 5%	kg/m ³	PN-EN ISO 1183-2
Transmittance	Not tested ⁴	± 4	%	ASTM D1003
Haze	Not tested ⁴	± 4	%	ASTM D1003
Clarity	Not tested ⁴	± 4	%	ASTM D1003
Corona treatment level ²	min. 38	—	mN/m	ISO 8296

¹ Film made of PE

² Constant level of corona treatment valid for three months

2. MECHANICAL PROPERTIES

Parameter	Value	Deviation	Unit	Methodology
Tensile at break: - lengthwise - crosswise	min. 30 min. 30	—	MPa	PN-EN ISO 527-3
Tensile at yield point: - lengthwise - crosswise	min. 4 min. 4	—	MPa	PN-EN ISO 527-3
Elongation at break: - lengthwise - crosswise	Depends on film thickness ⁴	—	%	PN-EN ISO 527-3
Coefficient of friction ³ : • static • dynamic	Not tested ⁴	—	—	PN-EN ISO 8295
Dart-drop	min. 500	—	g	PN-EN ISO 7765

³ Suited towards customer's needs

⁴ Tests are performed based on client's individual request

3. GUARANTEE UV

Suited towards customer's needs.

4. PACKAGING

Film on a paper core or on PVC core with diameter of 76 or 152 and placed on a pallet. Every roll is strictly labeled enabling production lot identification

5. APPLICATION

General packaging.

6. STORAGE

Film should be protected against atmospheric factors and be stored not longer than 24 months. Before usage film should be kept 24h at the pre-production place or in the production section.